



March 1st, 2023
Product Availability
Uniface 10
10.4.02-017

Sentinel License Manager:																																																	
Compatibility-code		W81	W10	W11	WN3	WN4	WN5	WN6	W81	W10	W11	WN3	WN4	WN5	WN6	LIE	LIE	LIF	LIG	LIF	LU7	LU8	RSG	RSH	SOF	WN4	WN6	WN6	LIE	LIE	LIF	LIG	LIF	LU7	LU8	AS5	AS6												
Stand-alone/Network		S	S	S	S	S	S	S	S	S	S	S	S	S	S	011	004	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S														
Cloud-served		S	S	S	S	S	S	S	S	S	S	S	S	S	S	011	004	S	S	-	-	S	S	S	S	011	004	S	S	S	S	S	S	S	S														
Cloud LM (+++)		S	S	S	S	S	S	S	S	S	S	S	S	S	S	011	004	S	S	-	-	008	008	008	008	008	008	008	008	008	008	008	008																
Build information:																																																	
Compatibility-code		W81	W10	W11	WN3	WN4	WN5	WN6	W81	W10	W11	WN3	WN4	WN5	WN6	LIE	LIE	LIF	LIG	LIF	LU7	LU8	RSG	RSH	SOF	WN4	WN6	WN6	LIE	LIE	LIF	LIG	LIF	LU7	LU8	AS5	AS6												
C/C++ compiler **		19.32.31329.0								19.32.31329.0								8.3.1	8.3.1	8.2.1	11.2.1	8.2.1	7.5.0	9.3.1	16.1	16.1	5.15	29.0	29.0	29.0	8.3.1	8.3.1	8.2.1	11.2.1	8.2.1	7.5.0	9.3.1	19.32.31329.0	19.32.31329.0	19.32.31329.0	8.3.1	8.3.1	8.2.1	11.2.1	8.2.1	7.5.0	9.3.1		

Notes:

S or Patch number = Supported with GA version Functionality has been verified

(S = Supported with E-distribution, patch number = support added from a specific patch number)

- = Not supported

S1 = For Windows 10 you need to use SDK 16.0 SP02 PL02 or higher.

S3 = Available for 64bit platforms only

* The WRD 6.4 is built using Java 8 targeting JRE 6 or higher and is verified using Tomcat 8. It requires a Java EE compliant web server that supports Servlet API, versions 2.3 through 3.1, using Java 6 or higher, preferably using the latest update of Java 8. For TLS connection with Uniface Router Java 8 or higher is required.

* The WRD 7.0 is built using JDK 11 targeting JRE 11 or higher and is verified using Tomcat 10. It requires a Jakarta EE compliant web server that supports Servlet API, versions 6.0 or higher, using Java 11 or higher, preferably using the latest version higher than Java 11. For TLS connection with Uniface Router Java 11 or

** Uniface C/C++ sources compiled with a C/C++ compiler depends upon the Operating System. Following compilers are used for the corresponding OS: MSVC for Windows, GCC for Linux, XL C/C++ for AIX, CCS C for Solaris. For compiling your 3GL applications we recommend to use the same or a compliant compiler version.

*** For Java Call-in, direct calls not using RMI are supported

(+) The Uniface Anywhere product itself is not part of the distribution; mentioned versions are current at release time of this Uniface release

(++) CEF: Uniface htmlwidget uses the CEF version 103.0.12 with corresponding Chromium version 103.0.5060.134

(+++) For using Cloud LM there are required extra manual steps.

NOTES:

Virtualization technologies: Uniface does not explicitly test or certify products running in virtual environments. More details are available on community.rocketsoftware.com/forums/uniface

Web browser Versions: We will provide support for browser versions which are generally available in the marketplace (and supported by the supplier). More details are available on community.rocketsoftware.com/forums/uniface

DBMS connectors are tested to work against the indicated client versions

DBMS Connectors are supported with local installations and AWS RDS instances